

MATERIAL SPECIFICATION SHEET

Vinyl Smooth - Type II 20 oz. Vinyl Wallcovering

Color.....	White
Roll Width	54" or 60"
Total Weight	20 oz. / Lineal Yard
Backing	Non-Woven
Breaking Strength, lbs. Force (Newton)	
Machine Direction.....	50 (222)
Cross Machine Direction	55 (245)
Tearing Strength, Scale	
Machine Direction.....	25
Cross Machine Direction	25
Coating Adhesion, lbs. Force for 1 Width	
Machine Direction.....	3
Coating Adhesion, Newtons for 2.5 cm	
Machine Direction.....	13.35
Abrasion Resistance, Double Rubs/Min.	
Machine Direction.....	300
Colorfastness to Light	
Machine Direction.....	200
Blocking, Scale Rating Max.	
Machine Direction.....	2
Crocking, Scale Rating Min.....	
Machine Direction.....	Good
Cold Crack Resitances, -20°F	
Machine Direction.....	No Change
Shrinkage, Percent Max.	
Machine Direction.....	2
Cross Machine Direction	1
Stain Resistance.....	
Machine Direction.....	1 - 12
Washability, Double Rubs/Min.....	100
Scrubability, Double Rubs/Min	300
Flame/Smoke Certifications.....	
Machine Direction.....	NFPA 265, CCCW 408 A, CCCW 408D, MEA No. 404-00-M

Contract Support Account Manager
 Phone: 216.432.1400 x.122
 Fax: 216.432.1500
 Email: contractsupport@4walls.com