

Product Specifications: Commercial Glitter® Vinyl Wallcovering

For Products

Glitter® Vinyl Murals

Physical Properties

DESCRIPTION Category V, Type II 20 oz. PVC-Vinyl Wallcovering

CONSTRUCTION Osnapburg-Backed Textured Vinyl with UV-LED Inks

SUBSTRATE

Roll Width 54" (1.37 m)

Weight 20 oz. per lineal yard

Face Bead Embossed PVC-Vinyl

Backing Polyester/Cotton Osnapburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A Fire Rated

NFPA 286 Corner Burn Test, Class A

NFPA 265 Corner Burn Test, Class A

CAN/ULC-S102.2 Passed requirements

BS476 Parts 6&7 Passed requirements

Mold and Mildew

ASTM G21 Passed requirements

Product Specifications: Commercial Glitter® Vinyl Wallcovering

Specifications

Federal Specifications:

GSA CCCW-408-D, Type II

WA Specifications:

WA-101, Type II

NSF/ANSI-342, Certified for Silver compliance

NFPA Life Safety Code 101

Passed requirements for flame and smoke

Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level