

Product Specifications: Commercial Smooth Vinyl Wallcoverings

For Products

Smooth Vinyl Murals

Physical Properties

DESCRIPTION Category V, Type II 20 oz. PVC-Vinyl Wallcovering

CONSTRUCTION Nonwoven-Backed PVC Vinyl with UV-LED Inks

SUBSTRATE

Roll Width 54" (1.37 m)

Weight 20 oz. per lineal yard

Face Smooth PVC-Vinyl

Backing Nonwoven

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A

EU Class Flame (EN15102), B-s1

CAN/ULC-S102.2 Passed requirements

BS476 Parts 6&7 Passed requirements

Mold and Mildew

ASTM G21 Passed requirements

Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics

Washability para. 7.4, 100 cycles: Passed all requirements

Scrubability para. 7.7, 300 cycles: Passed all requirements

Product Specifications: Commercial Smooth Vinyl Wallcoverings

Specifications

Federal Specifications:

GSA CCC-408-D, Type II

WA Specifications:

WA-101, Type II

NSF/ANSI-342, Certified for Silver compliance

NFPA Life Safety Code 101

Passed requirements for flame and smoke

Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

100% of backing fiber content is Post-Consumer

11% Post-Consumer content in total product using recycled polyester and cellulose

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level