

Product Specifications: Commercial Textured Vinyl Wallcoverings

For Products

Stipple Vinyl Murals
Semi-Smooth Vinyl Murals
Canvas Embossed Vinyl Murals

Physical Properties

DESCRIPTION.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering
CONSTRUCTION.....Osnaburg-Backed Textured Vinyl with UV-LED Inks

SUBSTRATE

Roll Width54" (1.37 m)
Weight20 oz. per lineal yard
FaceTextured PVC-Vinyl
BackingPolyester/Cotton Osnaburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers.
UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A
EU Class Flame (EN15102), B-s1
CAN/ULC-S102.2 Passed requirements
BS476 Parts 6&7 Passed requirements

Mold and Mildew

ASTM G21 Passed requirements

Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics
Washability para. 7.4, 100 cycles: Passed all requirements
Scrubability para. 7.7, 300 cycles: Passed all requirements

Product Specifications: Commercial Textured Vinyl Wallcoverings

Specifications

Federal Specifications:

GSA CCC-408-D, Type II

WA Specifications:

WA-101, Type II

NSF/ANSI-342, Certified for Silver compliance

NFPA Life Safety Code 101

Passed requirements for flame and smoke

Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level