

Product Specifications: High Performance Acoustical Wallcoverings

For Products

Standard and Custom Sibilance® High Performance Murals

Physical Properties

DESCRIPTION	100% Post-Industrial Recycled Polyester Felt in Graphic White
CONSTRUCTION	Dye-sublimated inks onto acoustically rated felt with post-treatment performance coating
SUBSTRATE	
Roll Width	63"
Roll Width	30 Yards
Weight	25 oz L/yd
Thickness	3.5 mm
Backing	Fused Polyester
INKS	Dye-Sublimation
COATING	Proprietary coating for lightfastness, wet and dry crocking

NRC

ASTM C-42320 (over gypsum board)

Flame & Smoke

ASTM-E84	Class A
Flame Spread	5
Smoke Developed.....	10
California Fire Code	CAL 117
ASTM-1353.....	Passed

Colorfastness
to Light

AATCC-16A Class 5 – 40 hours

Product Specifications: High Performance Acoustical Wallcoverings

Antimicrobial Properties

Fosshield® Antimicrobial Technology:

Silver & copper ions are incorporated into the polyester fiber and naturally attack microbes. Fosshield® inhibits the growth of bacteria, mold and fungus, providing permanent protection. Ions bind to any microbes that may be present on the fiber and disable their critical functions (metabolism, respiration, and reproduction).

Typical examples of microbes of common concern are Methicillin-resistant Staphylococcus aureus (MRSA), the Human rhinovirus (common cold), Streptococcus pyogenes (strep), Legionella pneumophila (Legionnaires disease), Human Coronavirus (SARS surrogate), and Feline Calicivirus (Norwalk virus).

Fosshield® is the technology incorporated into the FDA cleared SpectraShield® 9500 N95 surgical respirator mask. In the FDA testing, Fosshield® began microbe prevention immediately and eliminated 99.99% of certain odor-causing bacteria after one hour of contact with the respirator surface.

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level