

Product Specifications: High Performance IMO Vinyl Wallcoverings

For Products

IMO Vinyl Murals + WallMax®

Physical Properties

DESCRIPTION.....Category V, Type II 21 oz. PVC-Vinyl Wallcovering

CONSTRUCTION.....Osnaburg Backed Embossed PVC-Vinyl with UV-LED Inks and UV Matte Coating

SUBSTRATE

Roll Width54" (1.37 m)

Weight21 oz. per lineal yard

FaceTextured PVC-Vinyl

BackingPolyester/Cotton Osnaburg

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A

NFPA 286 Corner Burn Test, Class A

CAN S102M Tunnel Test, Class A

EU Classification in accordance with EN 13501

ASTM E603, Early Warning Effect® Life Safety and Property Protection

Mold and Mildew

ASTM G21 Passed requirements

Product Specifications: High Performance IMO Vinyl Wallcoverings

Specifications

Federal Specifications

GSA CCC-408A, Type II, Class A

WA Specifications

WA-101, Type II, Class A

NFPA 101 Life Safety Code

Meets requirements, NFPA 225, Class A

Interior Finish, IMO

Meets IMO FTP-Code, Annex 1, Parts 2 and 5

Environmental

Cadmium and Heavy Metal-free

Compliant with CHPS Section 01350

EU Toxicity compliant for EN 12149

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level