

## Product Specifications: Smooth High Performance Non-PVC Wallcoverings

For Products

**Smooth Carta® Murals + WallMax®**

Physical Properties

**DESCRIPTION**.....Type II, 17 mil Eco-Friendly PVC-Free Wallcovering

**CONSTRUCTION**.....Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

**SUBSTRATE**

Roll Width .....54" (1.37 m)

Weight .....290 g/m<sup>2</sup> per TAPPI T-410 Test Method

Face .....Latex-Saturated Wet-Strength Paper

Backing .....Textile Scrim

**INKS**

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

**COATING**

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 ..... Class A Fire Rated

Compliant with California Fire Code CA 1237

Compliant with IBC (International Building Code) sec. 803.1.1

Mold and Mildew

Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329

## Product Specifications: Smooth High Performance Non-PVC Wallcoverings

---

### Specifications

EN233 – Spongeability rating (wave 1), Excellent color fastness rating  
Carries the CE certification according to European Standard EN15102.

---

### Environmental

REACH compliant  
FSC®-certified paper  
Compliant with CHPS Section 01350

---

### Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit [findyourlevel.com](https://findyourlevel.com) for more information

 /leveldigitalwallcoverings

 @findyour\_level

 findyourlevel

 /findyour\_level