

Product Specifications: High Performance Smooth Silver Vinyl Wallcoverings

For Products

Smooth Silver Vinyl Murals + WallMax®

Physical Properties

DESCRIPTION.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering

CONSTRUCTION.....Nonwoven-Backed Smooth Silver PVC-Vinyl with UV-LED inks and UV Matte Coating

SUBSTRATE

Roll Width54" (1.37 m)

Weight20 oz. per lineal yard

FaceSmooth Silver Polyester over PVC-Vinyl

BackingNonwoven

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A

Flame Spread 25

Smoke Developed..... 105

Mold and Mildew

ASTM G21 Passed requirements

Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics

Washability para. 7.4, 100 cycles: Passed all requirements

Scrubability para. 7.7, 300 cycles: Passed all requirements

Product Specifications: High Performance Smooth Silver Vinyl Wallcoverings

Specifications

Federal Specifications:

GSA CCCW-408-D, Type II, Passed requirements

WA Specifications:

WA-101, Type II, Passed requirements

NSF/ANSI-342, Certified for Silver compliance

NFPA Life Safety Code 101

Passes all requirements for smoke and flame

Environmental

Low-VOC

EU Toxicity compliant

California Prop 65 compliant

Phthalate free, Cadmium and Lead-Free

100% of backing fiber content is Post-Consumer

11% Post-Consumer content in total product using recycled polyester and cellulose

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level