

Product Specifications: High Performance Textured Silver Vinyl Wallcoverings

For Products

Textured Silver Vinyl Murals + WallMax®

Physical Properties

DESCRIPTION.....Category V, Type II 23 oz. PVC-Vinyl Wallcovering

CONSTRUCTION.....Nonwoven-Backed Textured Silver PVC-Vinyl with UV-LED inks and UV Matte Coating

SUBSTRATE

Roll Width54" (1.37 m)

Weight23 oz. per lineal yard

FaceTextured Silver Mylar/PVC-Vinyl

BackingNonwoven polyester/cellulose 50% post-consumer recycled content

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

Flame & Smoke

ASTM-E84 Class A

Flame Spread 25

Smoke Developed..... 105

Mold and Mildew

ASTM G21 Passed requirements

Washability and Scrubability

ASTM F793 Standard Classification of Wallcovering by Characteristics

Washability para. 7.4, 100 cycles: Passed all requirements

Scrubability para. 7.7, 300 cycles: Passed all requirements

Product Specifications: High Performance Textured Silver Vinyl Wallcoverings

Specifications

Federal Specifications:
GSA CCC-408-D, Type II
WA Specifications:
NSF/ANSI-342 Certified

Environmental

Low-VOC
Phthalate free
Cadmium and Lead-Free
California Prop 65 compliant
50% of backing fiber content is Post-Consumer

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

 /leveldigitalwallcoverings

 @findyour_level

 findyourlevel

 /findyour_level