

Product Specifications: Commercial Non-PVC Wallcoverings

For Products

Smooth Carta® Murals
Textured Carta® Murals

Physical Properties

DESCRIPTION.....Type II, 14 oz. Eco-Friendly PVC-Free Wallcovering

CONSTRUCTION.....Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

SUBSTRATE

Roll Width54" (1.37 m)

Weight 14 oz. per lineal yard (22 mil)

FacePolyester/Natural Fiber Technology

BackingNonwoven 31% Post-Consumer Recycled Content

INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

Flame & Smoke

SUBSTRATE

ASTM-E84 Class A

CAN/ULC-S102..... Passed requirements

Mold and Mildew

ASTM E96 Permeability, 66 Perms Dry Cup Method, Passed WA-101 8 Perms

Product Specifications: Commercial Non-PVC Wallcoverings

Specifications

WA Specifications:
WA-101, Type II, Passed requirements
NSF/ANSI-342, Certified for Silver compliance

Environmental

Low-VOC
Prop 65 Compliant
Compliant with CHPS Section 01350
Recycled Content, 31% Post-Consumer

Free of PVC and POA (Olefin) Plasticizers, Phthalates, formaldehyde, Chlorine, Halogen, Heavy-Metals (Cadmium, Mercury, Lead, Zinc) Ozone Depleting Chemicals and Brominated flame retardants

LEED Eligibility

Product may contribute up to 2 LEED credits, conditionally, 2 other credits

- MR Credit 4.1 Recycled Content 20%
- MR Credit 4.2 Recycled Content 30%

Conditionally

- MR Credit 2.1 Contribution to project recycling program
- MR Credit 2.2 Contribution to project recycling program
- MR Credit 5.1 Manufactured local to new construction
- EQ Credit 4.1 Mounted with low emitting adhesives

Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit findyourlevel.com for more information

/leveldigitalwallcoverings

@findyour_level

findyourlevel

/findyour_level