

# Product Specifications: High Performance IMO Vinyl Wallcoverings

For Products

**IMO Vinyl Murals + WallMax®**

## Physical Properties

**DESCRIPTION**.....Category V, Type II 20 oz. PVC-Vinyl Wallcovering

**CONSTRUCTION**.....Osnaburg Backed Embossed PVC-Vinyl with UV-LED Inks and UV Matte Coating

### SUBSTRATE

Roll Width .....54" (1.37 m)

Weight .....20 oz. per lineal yard

Face .....Textured PVC-Vinyl

Backing .....Polyester/Cotton Osnaburg

### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

### COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

## Flame & Smoke

ASTM-E84 ..... Class A

NFPA 286 Corner Burn Test, Class A

CAN S102M Tunnel Test, Class A

EU Classification in accordance with EN 13501

ASTM E603, Early Warning Effect® Life Safety and Property Protection

## Mold and Mildew

ASTM G21 ..... Passed requirements

## Product Specifications: High Performance IMO Vinyl Wallcoverings

---

### Specifications

#### Federal Specifications

GSA CCC-408A, Type II, Class A

#### WA Specifications

WA-101, Type II, Class A

#### NFPA 101 Life Safety Code

Meets requirements, NFPA 225, Class A

#### Interior Finish, IMO

Meets IMO FTP-Code, Annex 1, Parts 2 and 5

---

### Environmental

Cadmium and Heavy Metal-free

Compliant with CHPS Section 01350

EU Toxicity compliant for EN 12149

---

### Questions?



Contact your Level Digital Wallcoverings [Sales Representative](#)



Visit [findyourlevel.com](https://findyourlevel.com) for more information

 /leveldigitalwallcoverings

 @findyour\_level

 findyourlevel

 /findyour\_level