

# level

## Product Specifications: Smooth Carta PVC-Free Wallcovering

---

### Physical Properties

**DESCRIPTION**.....Type II, 17 mil Eco-Friendly PVC-Free Wallcovering  
**CONSTRUCTION**.....Textile Scrim Backed PVC-Free Wallcovering with UV-LED Inks

#### SUBSTRATE

Roll Width .....54" (1.37 m)  
Weight .....290 g/m<sup>2</sup> per TAPPI T-410 Test Method  
Face .....Latex-Saturated Wet-Strength Paper  
Backing .....Textile Scrim

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

#### OPTIONAL WALLMAX COATING

Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.

---

### Flame & Smoke

ASTM-E84 ..... Class A Fire Rated  
Compliant with California Fire Code CA 1237  
Compliant with IBC (International Building Code) sec. 803.1.1

---

### Mold and Mildew

Highly Resistant – GREENGUARD Test method, GGTM.P040 per guidelines of ASTM D6329

---

### Specifications

EN233 – Spongeability rating (wave 1), Excellent color fastness rating  
Carries the CE certification according to European Standard EN15102.

---

### Environmental

REACH compliant  
FSC®-certified paper  
Compliant with CHPS Section 01350