

# level

## Product Specifications: Specialty Indoor Self-Adhesive

---

### Physical Properties

**DESCRIPTION**.....Matte White, Semi-Rigid Calendared PVC Vinyl

**CONSTRUCTION**.....Removable and repositionable acrylic pressure sensitive PVC vinyl with UV-LED inks

#### SUBSTRATE

Roll Width .....60"

Weight .....6.0 mil

Face .....Matte White Semi-Rigid PVC Vinyl

Backing .....Low-VOC, Acrylic Pressure-Sensitive Adhesive, with up to two-year removability

#### INKS

UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.

---

### Flame & Smoke

#### SUBSTRATE

ASTM E84 ..... Class A

ANSI/NFPA 255 ..... Class A

IFC 8-1 ..... Class A

Flame Spread..... 20

Smoke Developed ..... 120

---

### Durability

#### Temperature Range

Minimum Application: 32°F (0°C) \*

End Use: -40°F to 180°F (-40°C to 82°C)

#### Peel Adhesion lb./in.

Property: (N/25 mm) 180° on Stainless Steel - 24 hr.

Typical Values: 2.1 (9.2)

Test Method: ASTM D-903

#### Dimensional Stability, inches (mm)

48 hours @ 158°F

MD, 0.40

CD, 0.20

#### Shelf Life

2 years from Date of Manufacturer when store at 60 60/77°F (15/25°C) and 50% relative humidity

\*When applying at temperatures below 50°F the vinyl face may become brittle. Special care must be given during installation to keep substrate from tearing.