

# level

## Product Specifications: Textured Silver Vinyl Wallcoverings

---

Physical Properties	<p><b>DESCRIPTION</b>.....Category V, Type II 23 oz. PVC-Vinyl Wallcovering</p> <p><b>CONSTRUCTION</b>.....Nonwoven-Backed Textured Silver PVC-Vinyl with UV-LED Inks and UV Matte coating</p> <p><b>SUBSTRATE</b></p> <p>Roll Width .....54" (1.37 m)</p> <p>Weight .....23 oz. per lineal yard</p> <p>Face .....Textured Silver Mylar/PVC-Vinyl</p> <p>Backing .....Nonwoven polyester/cellulose 50% post-consumer recycled content</p> <p><b>INKS</b></p> <p>UV-LED inks with nearly zero VOC's containing up to 50% naturally-derived monomers and oligomers. UL GREENGUARD Gold Certified meeting California CDPH Standard Method v1.2, Classroom and Office Environment.</p> <p><b>OPTIONAL WALLMAX COATING</b></p> <p>Highly durable heavy metal free UV cured matte coating with fire retardancy, anti-microbial, mold and mildew resistant properties.</p>
Flame & Smoke	<p>ASTM-E84 ..... Class A</p> <p>CAN/ULC-S102.2 ..... Passed requirements</p>
Mold and Mildew	<p>ASTM G21 ..... Passed requirements</p>
Washability and Scrubability	<p>ASTM F793 Standard Classification of Wallcovering by Characteristics</p> <p>Washability para. 7.4, 100 cycles: Passed all requirements</p> <p>Scrubability para. 7.7, 300 cycles: Passed all requirements</p>
Specifications	<p>Federal Specifications:</p> <p>GSA CCC-408-D, Type II</p> <p>WA Specifications:</p> <p>NSF/ANSI-342 Certified</p>
Environmental	<p>Low-VOC</p> <p>Phthalate free</p> <p>Cadmium and Lead-Free</p> <p>California Prop 65 compliant</p> <p>50% of backing fiber content is Post-Consumer</p>